



Size	Load index	Speed Symbol	Section Width (mm)	Diameter (mm) Overall	Static Loaded Radius (mm)	Rolling Circ. (mm) @ 90 km/h (Tol. ± 2%)	Rim (Inch) Measuring	Rim (inch) Optional
9.5 R 17.5	129/127	M	240	842	391	2551	6.75	6.00
205/75 R 17.5	124/122	M	205	753	353	2297	6.00	5.25/6.75
215/75 R 17.5	126/124	M	212	767	359	2339	6.00	6.75
225/75 R 17.5	129/127	M	226	783	366	2388	6.75	6.00
235/75 R 17.5	132/130	M	233	797	372	2431	6.75	7.50
245/70 R 17.5	136/134	M	248	789	364	2406	7.50	6.75
265/70 R 17.5	138/136	M	262	817	376	2492	7.50	6.75
245/70 R 19.5	136/134	M	248	839	389	2559	7.50	6.75
265/70 R 19.5	140/138	M	262	867	401	2644	7.50	6.75/8.25
285/70 R 19.5	145/143	M	283	895	413	2730	8.25	7.50/9.00
305/70 R 19.5	148/145	M	305	923	424	2797	9.00	8.25
12 R 22.5	152/148	L	300	1084	504	3306	9.00	8.25
13 R 22.5	156/150	L	320	1124	521	3428	9.75	9.00
275/70 R 22.5	148/145	M	276	958	445	2922	8.25	7.50
295/80 R 22.5	152/148	M	298	1044	487	3184	9.00	8.25
305/70 R 22.5	150/148	M	305	1000	463	3050	9.00	9.25
315/70 R 22.5	152/148	M	312	1014	468	3093	9.00	9.75
		L						
315/80 R 22.5	154/150	M	312	1076	500	3282	9.00	9.75
	156/150	L						