



M840



| Size | Load index | Speed Symbol | Section Width (mm) | Diameter (mm) Overall | Static Loaded Radius (mm) | Rolling Circ. (mm) @ 90 km/h (Tol. ± 2%) | Rim (Inch) Measuring | Rim (inch) Optional |
|---------------|------------|--------------|--------------------|-----------------------|---------------------------|--|----------------------|---------------------|
| 10 R 17.5* | 143/141 | J | 254 | 858 | 398 | 2600 | 7.50 | 6.75 |
| 12.00 R 20 | 154/150 | K | 313 | 1122 | 515 | 3422 | 8.50 | 7.33/8.00/9.00 |
| | 156/150 | G | | | | | | |
| 9 R 22.5 | 133/131 | L | 230 | 970 | 455 | 2959 | 6.75 | 6.00 |
| 10 R 22.5 | 144/142 | K | 254 | 1020 | 476 | 3111 | 7.50 | 6.75 |
| 11 R 22.5 | 148/145 | K | 279 | 1050 | 489 | 3203 | 8.25 | 7.50 |
| | 145/142 | L | | | | | | |
| 12 R 22.5 | 152/148 | K | 300 | 1084 | 504 | 3306 | 9.00 | 8.25 |
| | 150/145 | L | | | | | | |
| 13 R 22.5 | 154/150 | K | 320 | 1124 | 521 | 3428 | 9.75 | 9.00 |
| | 156/150 | G | | | | | | |
| 275/70 R 22.5 | 148/145 | K | 276 | 958 | 445 | 2922 | 8.25 | 7.50 |
| 295/80 R 22.5 | 152/148 | K | 298 | 1044 | 487 | 3184 | 9.00 | 8.25 |
| | 150/145 | L | | | | | | |
| 315/80 R 22.5 | 156/150 | K | 312 | 1076 | 500 | 3282 | 9.00 | 9.75 |
| | 154/150 | M | | | | | | |
| | 152/148** | L | | | | | | |
| 12.00 R 24 | 156/153 | K | 313 | 1226 | 567 | 3739 | 8.50 | 8.00/9.00 |